



# Brisa® | Distressed



Ultrafabrics has met the significant challenge of enhancing the ever-popular **Brisa® | Distressed**. This new and improved construction not only takes **Distressed** to the next level of performance in upholstered seating, but it is now recognizable for its notable acoustical qualities!

This distinguished offering features a relaxed, rustic appeal and an authentic palette of earthy, leather-inspired hues.

Highlights include:

- Backcloth featuring our proprietary reinforced rayon blended with an added polyester content to provide greater durability, dimensional stability and recovery
- Improved seam strength
- Leading hydrolysis results, exceeding 14 weeks
- A breakthrough ventilation system elevates comfort by promoting airflow circulation and enhances softness for the ultimate seating experience
- Diminishes noise and absorbs sound transfer for quieter environments when combined with foam and/or paneling in vertical applications

An intelligent solution - recognized as the world's first breathable performance polyurethane, the **Brisa®** family of performance fabrics highlights boundary-pushing innovation where looks, feel and performance matter.



Acoustical



Breathable



Custom

# Brisa® | Distressed

## General Specifications

### Composition:

100% Polycarbonate Polyurethane Surface  
65% Polyester, 35% Rayon Backing

### Weight:

Approx. 9.3 oz. Per Square Yard  
Approx. 315 Grams Per Square Metre

### Thickness:

Approx. 1.0 Millimetres

### Width:

54 Inches / 137 Centimetres

## Performance

### Abrasion:

ASTM D4157 / 300,000 Double Rubs (Wyzenbeek)\*  
BS 2543 / 160,000 Rubs (Martindale)\*

\*meets or exceeds

### Hydrolysis:

14+ Weeks  
ASTM D3690-02 Sect. 6.11 (Hydrolytic Stability)  
ISO 1419 Method C (Accelerated Ageing)

### Adhesion of Coating:

ASTM D751

### Tear Strength:

ASTM D2261

### Breaking Strength:

ASTM D5034

### Air Permeability:

ASTM D737

### Sound Absorption:

ASTM C423

## Colorfastness

### Light Fastness:

AATCC 16.3, 200 Hours, Grade 4-5

### Crocking:

AATCC 8, Class 5 Wet & Dry

## Flammability

### F/R Rating:

- ASTM E84 (Adhered) - Class A
- CA TB 117-2013 - Pass
- FMVSS 302 & 95/28 Annex IV - Pass
- NFPA 260 - Class 1
- UFAC - Class 1

### Other Tests\*:

- ASTM E84 (Unadhered)
- BS 5852 PT 0, 1 & 5 (Crib 5)
- BS 5867 Part 2 Type B
- BS 7175
- California Technical Bulletin 133
- FAR Specifications
- IMO A.652 (16)
- NFPA 701

\*These fabrics, when treated and/or used with other compatible furniture components, have been shown to perform well under these fire test conditions.

## Earth Friendly

### • GREENGUARD Certified

- Meets stringent chemical emission limits including hazardous VOCs (ex. Formaldehyde)
- Promotes healthier indoor air quality
- Contributes towards satisfying credits under LEED® and level®, BIFMA

### • Compliant with Prop 65

- No Bisphenol A (BPA)
- No Conflict Minerals
- No Flame Retardants (Halogenated, Brominated: ex. PBDEs)
- No Heavy Metal Stabilizers
- No Plasticizer Phthalates
- No POPs (Persistent Organic Pollutants)
- No PVC (Polyvinyl Chloride)
- No toxic by-products
- Over 99% of solvents recaptured and recycled

For more information on our fabrics, cleaning and care instructions, please visit our website.



[www.ultrafabricsllc.com](http://www.ultrafabricsllc.com)

Ultrafabrics® and logo, and Brisa® are trademarks of Ultrafabrics Inc. Made in Japan.

7/17

